

# 3G Modular Converter Solutions

## MCS3 and MCS6 Series



### Features

- 19" sub-rack
- Modular 3U and 6U options
- Up to 6 converter modules
- N+1 redundancy options
- Pre-configured software
- High power density (110V/48V, 3kW, 6U, 19")
- Fast on-line expansion of modules (hot-swap)
- Graphical User Interface – LCD Panel
- Priority and non-priority options for DC distribution
- Remote monitoring & control via Ethernet
- Input for 12V, 24V, 48V, and 110V
- Output for 12V, 24V and 48V
- Color Coded Modules
- Integrated DC distribution panel
- Options for external Digital and Analogue I/O

12V, 24V, 48V and 110V secure DC-DC power converter systems up to 1.5kW and 3kW respectively.

The **Eaton® 3G Module Converter Solutions** are ideal for low to medium power telecommunications and industrial applications, offering compact, efficient, flexible and reliable secure DC power supply.

These 19" rack mount systems are available with up to 3 or 6 of the Eaton 3G Modular Converter Unit modules as 12V, 24V, 48V or 110V with an output up to 180A.

With efficiency up to 90% these modular converter solutions can reduce operating costs.

The systems include an integral DC distribution panel with a range of MCB and Low Voltage Disconnect (LVD) options available.

The SC200 series of system controller offers highly advanced control and monitoring features including Smart Alarm – a configurable logic for automated site energy control.

The SC200 also offers a complete array of communications options with Ethernet, GSM cellular (including text messaging) standard modem and TCP/IP communications options. The slightly lower specification SC100 may also be available as an option.

Typical applications include providing secure power for communications equipment, data networks, and industrial signalling and control.

The 3G Modular Converter Solutions are pre-configured and most system settings are adjustable in software and stored in transferable, configuration files for repeatable and quick one-step system set-up.



*Powering Business Worldwide*

# Technical Specifications

## Input

Nominal Voltage (DC)	12V, 24V, 48V, 110V (Depends on MCU modules fitted)
Voltage Range (DC)	12V, (10-15V) 24V, (20-30V) 48V, (40-60V) 110V, (80-130V)
Efficiency	85-90%

## Output

Nominal Voltage (DC)	12V, 24V, 48V (Depends on MCU modules fitted)
Voltage Range (DC)	12V, (12-15V) 24V, (23-32V) 48V, (44-56V)
Power (DC)	MCS3 12V:900W 24V:1500W 48V:1500W MCS6 12V:1800W 24V:3000W 48V:3000W
Load Regulation	< +/-0.5% (20-100% load)

## Environmental

Operating Temperature	-25 °C to +55 °C at rated power
Isolation	5kV DC input to output

## Mechanical

Dimensions H,W,D	MCS3-3G: 3U, 19" mounting, 306mm* MCS6-3G: 6U, 19" mounting, 306mm*
---------------------	--

*\*Additional clear space is required for exhaust air.*

## System

System Controller	SC200 or (SC100 option)
DC Distribution Module	MCS3-3G: 12-way load circuit breakers* MCS6-3G: 20-way load circuit breakers*

*\*Depends on pitch and rating of circuit breakers fitted and options fitted.*

Communications Features*	USB direct 10Base T Ethernet, TCP/IP, SNMP, Modbus-TCP, Modbus-RTU and on board web server. RS232 to external PSTN or GSM modem (modem not included) <i>*SC200 only</i>
Low Volts Disconnect (LVD)	MCS3-3G: optional 200A load disconnect MCS6-3G: optional 200A load disconnect
Blank Panels	For unused converter positions
Top/Rear Covers	Optional

## Software

DC Tools	Configuration software. Free download from: <a href="http://www.powerware.com/downloads">www.powerware.com/downloads</a>
----------	--

In the interests of continual product improvement all specifications are subject to change without notice. Performance ratings are valid with all other variables at Nominal. Specifications guaranteed over rated operating range. Images are indicative views only and not guaranteed representations and will vary according to options fitted.

